METAL PLESS


SPEC SHEET

MAXXPRO SIDEWALK WING

SIZES & SPECIFICATIONS

MODEL	AVAILABLE EDGES	BLADE DIMENSIONS			WING SIZE (EACH SIDE)	VEHICLE	APPLICATION	WING / GATE TYPE	APPROX. WEIGHT
		BOX	HEIGHT	EXTENDED					
PRO 0848-18 SW	HD - R OR L - HD - BOTH WINGS - LE - R OR L - LE - BOTH WINGS	8'	48"	18'	5'	WHEEL LOADER	25,000 lb - 50,000 lb	Hydraulic wings	4,600 lb (HD - R OR L, LE - R OR L) · 4,700 lb (HD - BOTH WINGS, LE - BOTH WINGS)
PRO 0848-20 SW	HD - R OR L - HD - BOTH WINGS - LE - R OR L - LE - BOTH WINGS	8'	48"	20'	6'		25,000 lb - 50,000 lb	Hydraulic wings	4,650 lb (HD - R OR L, LE - R OR L) · 4,750 lb (HD - BOTH WINGS, LE - BOTH WINGS)
PRO 1048-20 SW	HD - R OR L - HD - BOTH WINGS - LE - R OR L - LE - BOTH WINGS	10'	48"	20'	5'		25,000 lb - 50,000 lb	Hydraulic wings	5,000 lb (HD - R OR L, LE - R OR L) · 5,100 lb (HD - BOTH WINGS, LE - BOTH WINGS)
PRO 1048-22 SW	HD - R OR L - HD - BOTH WINGS - LE - R OR L - LE - BOTH WINGS	10'	48"	22'	6'		25,000 lb - 50,000 lb	Hydraulic wings	5,150 lb (HD - R OR L, LE - R OR L) · 5,200 lb (HD - BOTH WINGS, LE - BOTH WINGS)
PRO 1248-22 SW	HD - R OR L - HD - BOTH WINGS - LE - R OR L - LE - BOTH WINGS	12'	48"	22' (HD - R OR L) · 24' (HD - BOTH WINGS, LE - R OR L, LE - BOTH WINGS)	5' (HD - R OR L) · 6' (HD - BOTH WINGS, LE - R OR L, LE - BOTH WINGS)		30,000 lb - 50,000 lb	Hydraulic wings	5,360 lb (HD - R OR L, LE - R OR L) · 5,410 lb (HD - BOTH WINGS, LE - BOTH WINGS)
PRO 1248-24 SW	HD - R OR L - HD - BOTH WINGS - LE - R OR L - LE - BOTH WINGS	12'	48"	24'	6'		30,000 lb - 50,000 lb	Hydraulic wings	5,410 lb (HD - R OR L, LE - R OR L) · 5,510 lb (HD - BOTH WINGS, LE - BOTH WINGS)


AVAILABLE EDGES



HD

SOFT DRIVE TRIP EDGE

Unique Soft Drive trip edge design allows the individual sections to trip backward without the blade being lifted upward, greatly reducing the impact.



LE

LIVE EDGE

A floating soft drive steel trip edge with carbide inserts for longer wear life, that contours the unevenness of the ground for a cleaner result.