METAL PLESS

SPEC SHEET

SIDEMAXX-X


SIZES & SPECIFICATIONS

MODEL	AVAILABLE EDGES	BLADE DIMENSIONS		VEHICLE	APPLICATION	WING / GATE TYPE	APPROX. WEIGHT
		BOX	HEIGHT				
SDX 532	STD - With 3 Point Hitch (Category 2) - STD - With Trackless Coupler - STD - With Skid Steer Attachment - STD - With Tractor Subframe	5'	32"	WHEEL LOADER SKID STEER TRACTOR SIDEWALK VEHICLES	4,000 lb - 12,000 lb	6-position blade; no wings	580 lb (STD - With 3 Point Hitch (Category 2)) · 600 lb (STD - With Trackless Coupler) · 690 lb (STD - With Skid Steer Attachment) · 1,120 lb (STD - With Tractor Subframe)
SDX 532/LE	LE - With 3 Point Hitch (Category 2) - LE - With Trackless Coupler - LE - With Skid Steer Attachment - LE - With Tractor Subframe	5'	32"		4,000 lb - 12,000 lb	—	600 lb (LE - With 3 Point Hitch (Category 2)) · 640 lb (LE - With Trackless Coupler) · 790 lb (LE - With Skid Steer Attachment) · 1,220 lb (LE - With Tractor Subframe)
SDX 632	STD - With 3 Point Hitch (Category 2) - STD - With Trackless Coupler - STD - With Skid Steer Attachment - STD - With Tractor Subframe	6'	32"		4,000 lb - 12,000 lb	—	620 lb (STD - With 3 Point Hitch (Category 2)) · 660 lb (STD - With Trackless Coupler) · 750 lb (STD - With Skid Steer Attachment) · 1,180 lb (STD - With Tractor Subframe)
SDX 632/LE	LE - With 3 Point Hitch (Category 2) - LE - With Trackless Coupler - LE - With Skid Steer Attachment - LE - With Tractor Subframe	6'	32"		4,000 lb - 12,000 lb	—	630 lb (LE - With 3 Point Hitch (Category 2)) · 670 lb (LE - With Trackless Coupler) · 760 lb (LE - With Skid Steer Attachment) · 1,190 lb (LE - With Tractor Subframe)
SDX 732	STD - With 3 Point Hitch (Category 2) - STD - With Trackless Coupler - STD - With Skid Steer Attachment - STD - With Tractor Subframe	7'	32"		4,000 lb - 12,000 lb	—	690 lb (STD - With 3 Point Hitch (Category 2)) · 760 lb (STD - With Trackless Coupler) · 850 lb (STD - With Skid Steer Attachment) · 1,280 lb (STD - With Tractor Subframe)
SDX 732/LE	LE - With 3 Point Hitch (Category 2) - LE - With Trackless Coupler - LE - With Skid Steer Attachment - LE - With Tractor Subframe	7'	32"		4,000 lb - 12,000 lb	—	700 lb (LE - With 3 Point Hitch (Category 2)) · 770 lb (LE - With Trackless Coupler) · 860 lb (LE - With Skid Steer Attachment) · 1,290 lb (LE - With Tractor Subframe)

AVAILABLE EDGES



Standard trip edge allows the cutting edge to trip back.



A floating soft drive steel trip edge with carbide inserts for longer wear life, that contours the unevenness of the ground for a cleaner result.

BLADE POSITIONS



