METAL PLESS

SPEC SHEET

SIDEMAXX


SIZES & SPECIFICATIONS

MODEL	AVAILABLE EDGES	BLADE DIMENSIONS		VEHICLE	APPLICATION	WING / GATE TYPE	APPROX. WEIGHT
		BOX	HEIGHT				
SM 527/60	STD - With 3 Point Hitch (Category 2) - STD - With Trackless Coupler - STD - With Skid Steer Attachment - STD - With Tractor Subframe	5'	27"	WHEEL LOADER SKID STEER TRACTOR SIDEWALK VEHICLES	4,000 lb - 12,000 lb	No wings; optional hydraulic extension	550 lb (STD - With 3 Point Hitch (Category 2)) · 530 lb (STD - With Trackless Coupler) · 540 lb (STD - With Skid Steer Attachment) · 630 lb (STD - With Tractor Subframe)
SM 530/60LE	LE - With 3 Point Hitch (Category 2) - LE - With Trackless Coupler - LE - With Skid Steer Attachment - LE - With Tractor Subframe	5'	27"		4,000 lb - 12,000 lb	No wings; optional hydraulic extension	660 lb (LE - With 3 Point Hitch (Category 2)) · 625 lb (LE - With Trackless Coupler) · 905 lb (LE - With Skid Steer Attachment) · 1,060 lb (LE - With Tractor Subframe)

AVAILABLE EDGES



Standard trip edge allows the cutting edge to trip back.



A floating soft drive steel trip edge with carbide inserts for longer wear life, that contours the unevenness of the ground for a cleaner result.

BLADE POSITIONS

